



NSF-51 Certified Clear PVC Tubing, 80A

TUBE

Clear 80A (+/-3) FDA Grade
PVC

TEMP RANGE

+25 F to +150 F
-5 C to +65 C

REINFORCEMENT

No

RATINGS

NSF-51 Certified, USP Class
VI Rated Compound, FDA
Ingredients, Self Extinguishing

JACKET

None

CUSTOM OPTIONS

Refer to Custom Capabilities
page



NSF-51 Certified Clear PVC Tubing, 80A

ITEM NUMBER	ID	OD	WALL	*MAX WP	COLOR	PACKAGING
1100.0204.1001	1/8	1/4	0.062	65 PSI	Clear	100 ft Box
1100.0304.1001	3/16	1/4	0.032	50 PSI	Clear	100 ft Box
1100.0305.1001		5/16	0.062	55 PSI	Clear	100 ft Box
1100.0306.1001		3/8	0.094	60 PSI	Clear	100 ft Box
1100.0406.1001	1/4	3/8	0.062	55 PSI	Clear	100 ft Box
1100.0407.1001		7/16	0.094	58 PSI	Clear	100 ft Box
1100.0408.1001		1/2	0.125	60 PSI	Clear	100 ft Box
1100.0507.1001	5/16	7/16	0.062	50 PSI	Clear	100 ft Box
1100.0508.1001		1/2	0.094	55 PSI	Clear	100 ft Box
1100.0509.1001		9/16	0.125	60 PSI	Clear	100 ft Box
1100.0608.1001	3/8	1/2	0.062	45 PSI	Clear	100 ft Box
1100.0609.1001		9/16	0.094	50 PSI	Clear	100 ft Box
1100.0610.1001		5/8	0.125	55 PSI	Clear	100 ft Box
1100.0709.1001	7/16	9/16	0.062	35 PSI	Clear	100 ft Box
1100.0810.1001	1/2	5/8	0.062	30 PSI	Clear	100 ft Box
1100.0811.1001		11/16	0.094	40 PSI	Clear	100 ft Box
1100.0812.1001		3/4	0.125	45 PSI	Clear	100 ft Box
1100.1012.1001	5/8	3/4	0.062	25 PSI	Clear	100 ft Box
1100.1013.1001		13/16	0.094	35 PSI	Clear	100 ft Box
1100.1014.1001		7/8	0.125	40 PSI	Clear	100 ft Box
1100.1216.1000	3/4	1	0.125	35 PSI	Clear	100 ft Coil
1100.1418.1000	7/8	1 1/8	0.125	30 PSI	Clear	100 ft Coil
1100.1620.1000	1	1 1/4	0.125	25 PSI	Clear	100 ft Coil
1100.2024.1000	1 1/4	1 1/2	0.125	20 PSI	Clear	100 ft Coil
1100.2430.1000	1 1/2	1 7/8	0.187	30 PSI	Clear	100 ft Coil
1100.2432.1000		2	0.25	35 PSI	Clear	100 ft Coil
1100.3240.1000	2	2 1/2	0.25	30 PSI	Clear	100 ft Coil

* Working pressures shown are based at +68 F/+20 C