



## Natural NSF-51 Certified LLDPE Tubing

**TUBE**

Natural NSF-51  
Certified LLDPE

**TEMP RANGE**

-50 F to +140 F  
-45 C to +60 C

**REINFORCEMENT**

No

**RATINGS**

NSF-51 Certified

**JACKET**

None

**CUSTOM OPTIONS**

Refer to Custom Capabilities  
page



Natural NSF-51 Certified LLDPE Tubing

ITEM NUMBER	ID	OD	WALL	*MAX WP	COLOR	PACKAGING
2100.0004.1008	0.17	1/4	0.04	150 PSI	Natural	100 ft Bulk Box
2100.0004.7002						1,000 ft Spool
2100.0004.8002						2,000 ft Spool
2100.0204.1008	1/8	1/4	0.063	150 PSI	Natural	100 ft Bulk Box
2100.0204.7002						1,000 ft Spool
2100.0204.8002						2,000 ft Spool
2100.0305.1008	3/16	5/16	0.063	150 PSI	Natural	100 ft Bulk Box
2100.0305.7502						1,500 ft Spool
2100.0406.1008	1/4	3/8	0.063	150 PSI	Natural	100 ft Bulk Box
2100.0406.5002						500 ft Spool
2100.0406.7002						1,000 ft Spool
2100.0608.1001	3/8	1/2	0.063	150 PSI	Natural	100 ft Box
2100.0608.5002						500 ft Spool
2100.0810.1001	1/2	5/8	0.063	100 PSI	Natural	100 ft Box
2100.0810.5000						500 ft Coil
2100.1012.1000	5/8	3/4	0.063	75 PSI	Natural	100 ft Box
2100.1012.5000						500 ft Coil

\* Working pressures shown are based at +68 F/+20 C