



EVA Tubing 9%, 12%, 18% VA

TUBE

Natural and Black EVA

REINFORCEMENT

No

JACKET

None

TEMP RANGE

-50 F to +125 F
-45 C to +52 C

APPLICATIONS

Used in various agriculture industries. Can be used with ammonia nitrate, liquid fertilizers, NH₃ solutions, phosphoric acid, and several insecticides and pesticides. Black EVA has better UV resistance.



EVA Tubing, 9% VA

TUBE

Natural and Black EVA

REINFORCEMENT

No

JACKET

None

TEMP RANGE

-50 F to +125 F

-45 C to +52 C

APPLICATIONS

Used in various agriculture industries. Can be used with ammonia nitrate, liquid fertilizers, NH₃ solutions, phosphoric acid, and several insecticides and pesticides.

Black EVA has better UV resistance.



ITEM NUMBER	ID	OD	WALL	*MAX WP	COLOR	PACKAGING
3090.0608.3000	3/8	1/2	0.063	75 PSI	Natural	300 ft Coil
3099.0608.3000					Black	300 ft Coil
3090.0610.3000	3/8	5/8	0.125	125 PSI	Natural	300 ft Coil
3099.0610.3000					Black	300 ft Coil
3090.0810.3000	1/2	5/8	0.063	70 PSI	Natural	300 ft Coil
3099.0810.3000					Black	300 ft Coil
3090.0812.3000	1/2	3/4	0.125	125 PSI	Natural	300 ft Coil
3099.0812.3000					Black	300 ft Coil
3090.1216.3000	3/4	1	0.125	100 PSI	Natural	300 ft Coil
3099.1216.3000					Black	300 ft Coil
3090.1418.2000	7/8	1 1/8	0.125	100 PSI	Natural	200 ft Coil
3099.1418.2000					Black	200 ft Coil
3090.1620.2000	1	1 1/4	0.125	75 PSI	Natural	200 ft Coil
3099.1620.2000					Black	200 ft Coil

* Working pressures shown are based at +68 F/+20 C

EVA Tubing, 12% VA

TUBE

Natural and Black EVA

REINFORCEMENT

No

JACKET

None

TEMP RANGE

-50 F to +125 F

-45 C to +52 C

APPLICATIONS

Used in various agriculture industries. Can be used with ammonia nitrate, liquid fertilizers, NH₃ solutions, phosphoric acid, and several insecticides and pesticides.

Black EVA has better UV resistance.



ITEM NUMBER	ID	OD	WALL	*MAX WP	COLOR	PACKAGING
3120.0608.3000	3/8	1/2	0.063	75 PSI	Natural	300 ft Coil
3129.0608.3000					Black	300 ft Coil
3120.0610.3000	3/8	5/8	0.125	125 PSI	Natural	300 ft Coil
3129.0610.3000					Black	300 ft Coil
3120.0810.3000	1/2	5/8	0.063	70 PSI	Natural	300 ft Coil
3129.0810.3000					Black	300 ft Coil
3120.0812.3000	1/2	3/4	0.125	125 PSI	Natural	300 ft Coil
3129.0812.3000					Black	300 ft Coil
3120.1216.3000	3/4	1	0.125	100 PSI	Natural	300 ft Coil
3129.1216.3000					Black	300 ft Coil
3120.1418.2000	7/8	1 1/8	0.125	100 PSI	Natural	200 ft Coil
3129.1418.2000					Black	200 ft Coil
3120.1620.2000	1	1 1/4	0.125	75 PSI	Natural	200 ft Coil
3129.1620.2000					Black	200 ft Coil

* Working pressures shown are based at +68 F/+20 C

EVA Tubing, 18% VA

TUBE

Natural and Black EVA

REINFORCEMENT

No

JACKET

None

TEMP RANGE

-50 F to +125 F

-45 C to +52 C

APPLICATIONS

Used in various agriculture industries. Can be used with ammonia nitrate, liquid fertilizers, NH₃ solutions, phosphoric acid, and several insecticides and pesticides.

Black EVA has better UV resistance.



ITEM NUMBER	ID	OD	WALL	*MAX WP	COLOR	PACKAGING
3180.0608.3000	3/8	1/2	0.063	75 PSI	Natural	300 ft Coil
3189.0608.3000					Black	300 ft Coil
3180.0610.3000	3/8	5/8	0.125	125 PSI	Natural	300 ft Coil
3189.0610.3000					Black	300 ft Coil
3180.0810.3000	1/2	5/8	0.063	70 PSI	Natural	300 ft Coil
3189.0810.3000					Black	300 ft Coil
3180.0812.3000	1/2	3/4	0.125	125 PSI	Natural	300 ft Coil
3189.0812.3000					Black	300 ft Coil
3180.1216.3000	3/4	1	0.125	100 PSI	Natural	300 ft Coil
3189.1216.3000					Black	300 ft Coil
3180.1418.2000	7/8	1 1/8	0.125	100 PSI	Natural	200 ft Coil
3189.1418.2000					Black	200 ft Coil
3180.1620.2000	1	1 1/4	0.125	75 PSI	Natural	200 ft Coil
3189.1620.2000					Black	200 ft Coil

* Working pressures shown are based at +68 F/+20 C