



NSF-51 Certified Silicone Tubing

TUBE

Translucent natural 50A (+/-3)
NSF-51 Certified Silicone

REINFORCEMENT

No

JACKET

None

TEMP RANGE

-100 F to +500 F
-73 C to + 260 C

RATINGS

NSF-51 Certified, USP Class
VI Rated Compound, FDA
Ingredients, Self Extinguishing



NSF-51 Certified Silicone Tubing

ITEM NUMBER	ID	OD	WALL	*MAX WP	COLOR	PACKAGING
8100.0102.1001	1/16	1/8	.031	10 PSI	Natural	100 ft Box
8100.0204.1001	1/8	1/4	.062	20 PSI	Natural	100 ft Box
8100.0304.1001	3/16	1/4	.032	5 PSI	Natural	100 ft Box
8100.0305.1001		5/16	.062	20 PSI	Natural	100 ft Box
8100.0306.1001		3/8	.094	20 PSI	Natural	100 ft Box
8100.0406.1001	1/4	3/8	.062	5 PSI	Natural	100 ft Box
8100.0407.1001		7/16	.094	20 PSI	Natural	100 ft Box
8100.0408.1001		1/2	.125	15 PSI	Natural	100 ft Box
8100.0507.1001	5/16	7/16	.062	10 PSI	Natural	100 ft Box
8100.0508.1001		1/2	.094	10 PSI	Natural	100 ft Box
8100.0608.1001	3/8	1/2	.062	10 PSI	Natural	100 ft Box
8100.0609.1001		9/16	.094	10 PSI	Natural	100 ft Box
8100.0610.1001		5/8	.125	10 PSI	Natural	100 ft Box
8100.0810.1001	1/2	5/8	.062	5 PSI	Natural	100 ft Box
8100.0811.1001		11/16	.094	5 PSI	Natural	100 ft Box
8100.0812.1001		3/4	.125	10 PSI	Natural	100 ft Box